












PRODUCT	PART #	DESCRIPTION	
	<p>6000T</p> <p>6000</p> <p>6100</p> <p>6100T</p> <p>6100T</p> <p>6100T</p> <p>6003</p> <p>6100UPG</p> <p>6500</p> <p>6502</p>	<p><u>ENTERPRISE 101 - NETWORK PAGING SOFTWARE</u></p> <p>Enterprise 3 Concurrent User License with Z-100 UHF TX (does not include web interface)</p> <p>Enterprise Three (3) User (Software Only)</p> <p>Enterprise Unlimited User (Software Only)</p> <p>Enterprise Unlimited User License with Z-100 UHF TX (page 3)</p> <p>Enterprise Unlimited User License with Z-500 UHF TX (page 4)</p> <p>Enterprise Unlimited User License with Z-500PRO UHF TX</p> <p>Note: Unlimited User License Includes Web Interface</p> <p>Enterprise Email Interface (optional)</p> <p>(Enterprise 101 Email Interface is both an email client (able to send emails) and an email server (able to receive email for dispatch to mobile recipients).</p> <p>Upgrade to Latest Version (Within 1 year)</p> <p><u>INTERFACE PAGING SOFTWARE</u></p> <p>Interface Paging Software (includes 3 inputs/outputs)</p> <p>Interface Paging Software Upgrade (adds 1 input/output).</p>	<p><u>ENTERPRISE 101 SOFTWARE</u></p> <ul style="list-style-type: none"> • Send custom messages to on-site pagers, cell phones, PDA's and Wide Area Pagers; • Message retrieval and message history; • Reminder messages and schedules calls; • Simple 'Click & Point' user interface; • Reduces the number of calls to mobile phones;
 	<p>9470</p> <p>9457</p> <p>9475</p> <p>9460</p> <p>9465</p>	<p><u>INTELPage TRANSMITTER</u></p> <p>INTELPage 5 UHF Rack Mount Only</p> <p>INTELPage 5 UHF Desktop/Wall Mount</p> <p>INTELPage 25 UHF Rack Mount Only</p> <p><u>INTELPage IP TRANSMITTER</u></p> <p>INTELPage IP 5 UHF Rack Mount</p> <p>INTELPage IP 25 UHF Rack Mount</p>	<p><u>INTELPAGE</u></p> <ul style="list-style-type: none"> • Synthesized Paging Transmitter (desktop) • Works well with advanced features of Messenger • Providing messaging across multiple sites, entire cities, states, nationwide • Connect to other modules in Fusion series • Includes serial port to receive & relay messages that use suitable protocols • Supports 1,000 pager IDs
	<p>9454</p> <p>9454D</p> <p>9465E</p> <p>9466</p> <p>9467</p>	<p><u>EVENT MANAGEMENT MODULE - Base Package</u> <i>Includes 4 Concurrent User Client Licenses - 100 Recipient Licenses & POCSAG Output Port</i> <i>Maximum capacity of 3 ports + 1 TAP or telephony port.</i></p> <p>EMMR - Rack Mount Module</p> <p>Event Management Module – Desktop/Wall Mount</p> <p>EMM - Email Interface</p> <p>EMM - Generic Interface</p> <p>EMM - Tap Interface</p>	<p><u>THE EVENT MANAGEMENT MODULE</u> Base Package contains a central data base for up to 10,000 individual and group contacts. Provides easy access up to 100 commonly used text messages and also displays the status for messages recently sent and received through the system.</p>
	<p>9468</p> <p>9469</p>	<p>EMM - Telephone Interface Module (TIM)</p> <p>EMM - Additional PBX Ports</p>	

PRODUCT	PART #	DESCRIPTION	
	9485 9476 9477 9478 9452 9453	<p><u>EMM - License Upgrades</u></p> <p>EMM - 5 Additional Concurrent Client User Licenses EMM - 100 Additional Recipient Licenses EMM - 500 Additional Recipient Licenses EMM - 1000 Additional Recipient Licenses</p> <p><u>ALARM DISPATCH MODULE</u></p> <p>Alarm Dispatch Module - Rack Mount - Contact Closure Alarm Dispatch Module - Rack Mount - Opto Coupled</p>	<p><u>THE ALARM DISPATCH MODULE (ADM)</u> is capable of taking data from various resources such as Nursecall and building management systems to security and fire alarms.</p> <p>Connecting multiple ADMs via RS485 lets you expand the number of opto-coupled or dry contact inputs on your system to provide the ideal messaging solution.</p> <p><u>PC PAGING:</u> Use a simple Windows user interface to configure the software; easy to set up and use. Multilingual capabilities, plug and play unit setup and complete control over configuration to make getting connected trouble-free.</p>
	9455R	<p><u>CELLULAR MESSAGING MODULE</u></p> <p>CMM - Rack Mount 850/1900 Band</p>	<p><u>THE CELLULAR MESSAGING MODULE (CMM)</u> lets you send short messages (SMS) to cellular telephones and other SMS compliant devices.</p> <p>The CMM can be connected to the Alarm Dispatch Module.</p> <p>Connect the CMM to fire alarms and send SMS alerts direct to officers carrying cell phones; connect to electrical equipment for maintenance alerts; and so much more.</p> <p>Once connected with a valid SIM card, the CMM is designed to need no more intervention from the user.</p>
	5500 5510 5520 5530 5541	<p><u>MAXPAGE</u></p> <p>MAXPage UHF Standard Alphanumeric Transmitter <i>Includes Antenna & Internal Power Supply</i></p> <p><i>Options Available for MAXPage Standard</i></p> <p>Telephone Interface - PABX Port MAXPage Serial Interface for MP Standard, includes serial cable Alphanumeric Keyboard Port - Keyboard not included MAXPage Voice Paging for MAXPage</p>	<p><u>MAXPAGE:</u></p> <ul style="list-style-type: none"> • 2 to 4 watt switchable transmitter • 999 pager capacity • Operate with voice pagers, flash & vibrate coasters, alphanumeric pagers with optional software. • Voice prompted telephone (PABX) interface (optional) • Backlit 32 character LCD display and keypad • 4 dry contact alarm point inputs
	1166	<p><u>Z-100 TRANSMITTER</u></p> <p><i>Includes Antenna, Power Supply & Serial Cable</i></p>	<p><u>Z100 TRANSMITTER</u></p> <ul style="list-style-type: none"> • 2/5 Watt Paging Transmitter w/RS232 nine pin serial port. • Supports TAP, Comp1, Comp2 & Scope Protocol. • PC Programming available. • 999 Pager Capacity
	6200-8	<p><u>Z-500 ALPHANUMERIC TRANSMITTER</u></p> <p><i>Includes Antenna, Power Supply & Serial Cable</i></p>	<p><u>Z-500 A/N TRANSMITTER</u></p> <ul style="list-style-type: none"> • Economical, eliminates wide area paging service fees • Integrate with NurseCall Systems • Long range campus wide coverage (2/ 5 watt system provides up to 2 mile coverage, depending upon terrain) • Supports alphanumeric, numeric, and tone only messages • Supports paging RF data rates of 512, 1200, and 2400 bps • Industry compatibility using the TAP, Scope, Comp1 & Comp2 protocols serial data interface • Pager database can be programmed into on-board EEPROM using Windows based programming software, included with each system.


PRODUCT	PART #	DESCRIPTION	
	6200PRO	<p><u>Z-500PRO DUAL PORT A/N TRANSMITTER</u></p> <p><u>Includes Antenna, Power Supply & Serial Cable</u></p>	<p><u>Z-500PRO</u></p> <p>Dual RS-232 Com Ports (DB-9 Female) Can be used with 2 Different Host Systems such as 2 Nurse Call Systems or 1 Nurse Call System with Enterprise 101 Software without the need of a Port Concentrator or Port Monitoring/Routing Software. Eliminates wide area paging service fees. Campus wide coverage of up to 3 miles, depending on</p>
	<p>1167</p> <p>5710</p> <p>5715</p> <p>5812</p> <p>5716</p>	<p><u>AMPLIFIERS</u></p> <p>5 Watt Amplifier</p> <p>50 Watt Amplifier</p> <p>100 Watt Amplifier</p> <p>175 Watt Amplifier</p> <p>Power Supply for 50 and 100 Watt Amplifiers</p>	
	<p>6300</p> <p>6301</p> <p>6302</p>	<p><u>ALARM MONITORING SYSTEM</u></p> <p>D/V-64 Alarm Monitoring System</p> <p>D/V-64EM Expanded Units - 64 points each (as extensions of Maser Unit D/V-64)</p> <p>The expansion modules may be connected to the main unit to increase the quantity of inputs up to 1,024 points. Expansion modules are connected via a 3-wired RS-485 connection.</p> <p>D/V-64RM Connection to Master Unit for dialing to remotely located paging terminal</p>	<p><u>D/V-64</u> is a <u>Text Messaging Device</u> that monitors information from critical operating systems and machines and delivers it to people who need it.</p> <p><u>Dry Contact / Wetted Voltage Inputs:</u> D/V-64 is equipped with 64 dry or wetted voltage inputs. User defined messages of up to 80 characters are sent to a designated message receiver when there is a status change on any of the inputs.</p> <p><u>Critical System Information and Events</u> are delivered to widely available and well accepted wireless messaging tools. Users of portable messaging devices such as pagers, cell phones. Information can also be received on electronic display boards (LED).</p>
	6303	D/V-8/232 Printer Port Paging Interface	<p><u>D/V-8/232</u> is a text messaging device that monitors information from critical operating systems and machines, and delivers it to the people who need it.</p> <p>The D/V-8/232 is equipped with 8 dry contact or wetted voltage input. User defined messages of up to 80 characters are sent to a designated message receiver when there is a status change on any of the input.</p> <p>Users of portable messaging devices such as pagers, Cell Phones can receive information from monitored systems while they are mobile</p>
	<p>1162A</p> <p>1162PS</p> <p>1164</p> <p>1164D</p>	<p><u>SILENTPage PAGING SYSTEM</u></p> <p>SilentPage I Tone / Vibe Transmitter</p> <p>AC Adapter/Power Supply</p> <p>SilentPage II Numeric Transmitter</p> <p>SilentPage II Numeric Transmitter w/Telephone Interface (DTMF)</p>	<p><u>SILENTPAGE PAGING SYSTEM:</u></p> <ul style="list-style-type: none"> • Up to 1 mile radius • 899 Pager Capacity • Large Backlight LCD Display • Sends Alerts to Pagers or Coasters


PRODUCT	PART #	DESCRIPTION	
	1165	<p><u>SILENTPAGE PAGE ALPHA</u></p> <p>SilentPage Alpha Transmitter w/Keyboard</p>	<p><u>SILENTPAGE PAGE ALPHA:</u></p> <ul style="list-style-type: none"> • Send custom text messages • 99 canned messages • 7 dry contacts for quick paging of Alarm Panels, Machinery, Doors, etc.
	<p>3100</p> <p>3401</p> <p>3403</p> <p>3404</p> <p>3408</p> <p>3405</p> <p>LITARR</p> <p>LMR-195</p> <p>LMR-600</p> <p>4402</p> <p>HCC5</p>	<p><u>ANTENNAS</u></p> <p>UHF 1/4 wave antenna</p> <p>UHF 1/2 wave, 2.5 dB gain, 8" Flexible, BNC Connector</p> <p>77" 5 dB gain antenna</p> <p>Exterior Bracket to fit 77" antenna</p> <p>12" Interior Wall Mounting Bracket for 77" Antenna</p> <p>Base Omni, Unity Antenna @450-479 Freq.</p> <p>Lightning Arrestor</p> <p style="text-align: center;">Other Antennas Available Depending on Application - Call for Pricing</p> <p><u>ANTENNA CABLES</u></p> <p>LMR 195 - 15 Ft. Cable - with fittings</p> <p>LMR 600 Shielded Cable \$4.00 Per Foot + \$50.00 for connection fittings</p> <p>Male to Male Gender Changer</p> <p>Hardline Copper Clad 7/8" Thick Cable \$6.50 Per Foot + \$80.00 for connection fittings</p>	<p><u>77" 5 DB GAIN ANTENNA TECHNICAL DATA:</u></p> <p>Max. Input Power: <u>250</u> Watts Bandwidth >1.5 VSWR: <u>10</u> Flexible Extension: <u>Jumper w/N Male N Female</u> (Optional) Overall Length: <u>6.4</u> feet Wind Velocity Rated: <u>100</u> MPH Wind Load: <u>.35</u> sq. ft. Finish: <u>Aluminum</u> Lightning Protect: <u>DC</u> Ground Lateral Thrust @RWV: <u>12.6</u> lbs Weight: <u>4</u> lbs</p>
	3407	<p><u>YAGI ANTENNA</u></p> <p>Includes mounting hardware</p>	<p><u>YAGI ANTENNA TECHNICAL DATA:</u></p> <ul style="list-style-type: none"> • Mounting: <u>Stainless Steel</u> • Elements: <u>3/8"</u> diameter solid 6061 - T6 • Finish: <u>Protective Gold or Black anodized</u> finish • Max. Power: <u>300</u> watts • VSWR: <u><1.5:1</u> • db Gain: <u>7.1</u> • Impedance: <u>50</u> ohms • Mountg Power: <u>Up to 1-5/8"</u> mast • Tuning: <u>Pre-tuned</u> on a network analyzer • Termination Type: <u>N</u> female • Boom Lenth: <u>3</u> Element - 20-3/16" <u>6</u> Element - 44" • Wind Survival: <u>100</u> MPH
<p>Staff Paging System</p> 	7900	<p><u>16 BUTTON MEDICAL/HOSPITALITY STAFF OR EXAM ROOM STAFF PAGING SYSTEM</u></p> <p style="text-align: center;">Exam Room Staff Paging System</p> 	<p><u>16 BUTTON STAFF CALL:</u></p> <ul style="list-style-type: none"> • The UHF Medical & Hospitality Staff Call System was designed to help staff operate much more efficiently and provide better customer service. <p><u>THE STAFF CALL SYSTEM</u></p> <ul style="list-style-type: none"> • Was designed to help medical staff operate much more efficiently and provide more effective staff communication. • Staff is immediately alerted in under 2 seconds when a button is pressed beside their name. • Also sends messages to wireless LED Signs.

PRODUCT	PART #	DESCRIPTION	
	8900	<p><u>9 BUTTON STAFF CALL PAGING SYSTEM</u></p>	<p><u>9 BUTTON STAFF CALL PAGING SYSTEM:</u></p> <ul style="list-style-type: none"> • 9 Button on-site paging system is designed to directly page staff in under 2 seconds. • The individual call button features can transmit an Alert to a single pager or group of pagers. • Mounting brackets, power supply & antenna included.
	<p>1160A 1160B 1160C 1160D</p>	<p><u>PORTABLE SILENTPAGE TRANSMITTER</u></p> <p>Portable Wireless Transmitter - 1 Button Portable Wireless Transmitter - Four Button Portable Wireless Transmitter - Eight Button Programmer (Optional)</p>	<p><u>PORTABLE SILENT PAGE TRANSMITTERS</u></p> <ul style="list-style-type: none"> • Are a one touch solution to alert an alphanumeric or numeric pager instantly. • Portable Wireless Transmitters comes in 4-button, and 8-button models • Each button is programmed to send a specific preprogrammed message to a pager. • The preprogrammed messages can be as long as 130 alpha or 2000 numeric characters.
	<p>1161-1 1161-D</p>	<p><u>I-PAGE SINGLE BUTTON PORTABLE TRANSMITTER</u></p> <p>I - Page Single Button Portable Transmitter Programmer (Optional)</p>	<p><u>I-PAGE PORTABLE TRANSMITTER</u></p> <ul style="list-style-type: none"> • Frequency Range (TX):_450 – 470 MHz • Module Type:_____FSK • Output Power (EIRP):___+28dbm (500mW) • Baud Rate:_____512/1200/2400 bits • Antenna:_____SMA/M • Character Mode:_____Numeric, Alpha or Tone-Only • Maximum Characters:___120 • Low Battery Warning Message:___Auto send (optional) • Battery Low Detect Voltage: ___3.5+/-0.1V • Configuration Interface:___Mini USB Through PC • Power Supply:_____Rechargeable Battery
	<p>2018 2018H 2218 2680</p>	<p><u>WIRELESS PENDANTS</u></p> <p>Wireless Pendant with Necklace (1 - 19)(20 or more)</p> <p>Wireless Pendant Wall Mount (included)</p> <p>Programming Software includes USB Cable (Optional)</p> <p>Wireless Repeater</p> 	<p><u>WIRELESS PENDANTS:</u></p> <ul style="list-style-type: none"> • Frequency: 410–490MHz. 1 Channel Crystal controller. • Baud rate: 512bps / 1200bps / 2400bps. • Message: Numeric and Alphanumeric (Max 40 Character). • RF output 10 mW (+10.0 db). • Battery: Type 23A Alkaline battery. • Programming I/O: via USB with P/C. • Size: 3.15" X 1.65" X .071" • Housing Color: White • Model Weight: (with battery) 1.12 oz

PRODUCT	PART #	DESCRIPTION	
	<p>814DR</p> <p>812PR</p> <p>814S</p> <p>813S</p>	<p><u>PAGING DATA RECEIVER (OPTIONAL)</u></p> <p>The Paging Data Receiver is a multi-function Paging Receiver capable of receiving paged messages and Processing them in a variety of ways.</p> <p>It is able to print messages direct to a parallel or serial printer or output the message data via a serial port.</p> <p><u>PROGRAMMING SOFTWARE KIT W/CABLES</u></p> <ul style="list-style-type: none"> • Paging Printer • Paging Logger to PC <p><u>MESSAGING LOGGING & FILTERING SOFTWARE (SINGLE USER)</u></p> <p>Reporting ability of incoming calls. Report can be transported via email to an address at a specified time.</p> <p><u>MESSAGING LOGGING & FILTERING SOFTWARE (5 USER)</u></p>	<p><u>PDR APPLICATIONS</u></p> <ul style="list-style-type: none"> • Messag Monitoring & Printing • Data Transfer • NurseCall <p>Features:</p> <ul style="list-style-type: none"> • Text search and replace • Relay control by message or individual by capcode • Inbuilt Pocsag Encoder • Time and date stamping of messages • Parallel printer output • Serial data port (2 optional) • External antenna on BNC connector • Power Requirements 12 volt DC • Very large number of cap codes (>2000) • Physical (provisional) 8.66 x 2.76 x 1.18 inches. • Battery backed real time clock
	<p>2175A</p> <p>2173</p> <p>2172</p> <p>2171</p>	<p><u>NUMERIC PAGERS</u></p> <p>TRIDENT Button Programmable Numeric Pager 1 to 24</p> <p>25 to 49 =</p> <p>50 to 99 =</p> <p>100 +</p> <p>TRIDENT Pager Holster</p> <p>TRIDENT Battery Cover</p> <p>TRIDENT Programmer (Optional)</p>	<p><u>NUMERIC PAGERS:</u></p> <ul style="list-style-type: none"> • Large LCD display, 12 digits and 10 icons • 6 message memories, 25 digits per memory, total 400 digit memory capacity • Time stamp (12/24), week, day and month (calendar) display function • Message stamp function • Auto on/off function • Three sets of alarm clock timer setting • Duplicate message indication • Unread message indication (every 10 minutes) • Option to delete individual message or erase all • 10 tones and melodies in alert function • Vibration alert function • Silent receiving function • Illuminating backlight for easy night reading • Low battery indication • Dimensions: 35 X 50 X 18 mm • Weight: 40g (without battery) • Available in VHF 138-174 MHz and UHF 410-510 MHz
	<p>2165</p> <p>2165CH</p>	<p><u>REC-10 RECHARGEABLE NUMERIC PAGER</u></p> <p>REC10 Rechargeable Numeric Pagers</p> <p>REC10 Charger Rack (hold 10 pagers)</p>	<p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Top Read • Slide Switch Select Beep, Vibration, or Off • Loud Buzzer, Strong Vibration • AA Battery • 16 Memory Slots • Back-light Display • Slide Switch Select Beep or Vibration Alert • Date and Time Display • Message Time stamping • Message Lock • Selective Erase All • Memory Retention • Lithium Battery Backup • Reminder Alert • Low Battery Indicator • Display 12 Digits

PRODUCT	PART #	DESCRIPTION	
	<p>2190</p> <p>2188</p> <p>2187H</p> <p>2186</p>	<p>ALPHANUMERIC PAGERS</p> <p>ENTERPRISE 2/4 Line Button Programmable Pager 1 to 24</p> <p>25 to 49 =</p> <p>50 to 99 =</p> <p>100 +</p> <p>Battery Cover</p> <p>Holster for Enterprise A/N Pager w/Lens cover</p> <p>ENTERPRISE Programmer (Optional)</p>	<p>ALPHANUMERIC PAGER:</p> <ul style="list-style-type: none"> • Unread message reminder alert every 3 minutes • Battery voltage measuring function • Date and Time display • Smart LCD screen that displays 112 x 32 dots, • Message Lock function • Date and Time Stamping of message • Duplicate message indication • Low battery alert • Option to delete individual message or erase all • Selectable alert mode, 4 kinds of beep tones, 10 kinds of Melodies, vibration and silent • Alarm function • Automatic power on/off (silent receiving)
	<p>2871</p> <p>2871H</p> <p>2871PR</p>	<p>Gold Alphanumeric Pager - Intrinsically Safe</p> <p>Gold A/N Pager Holster</p> <p>Gold A/N Programmer (Optional)</p> <p>Pager Programming</p>	<p>GOLD A/N PAGER:</p> <ul style="list-style-type: none"> • 4 lines, 84 alphanumeric one page display • 16 memory slots • Reminder Alert/Zoom Feature • Selective PC or Hand Programming • Intrinsically Safe
	<p>7810</p> <p>7810H</p> <p>7810PR</p>	<p>CHAMP IV - 4 Line Alphanumeric Pager</p> <p>Champ IV Pager Holster</p> <p>CHAMP Programmer (Optional)</p>	<p>CHAMP IV - 4 LINE A/N PAGER</p> <ul style="list-style-type: none"> ▪ 4 /8 Line Alpha Display (user selectable). ▪ 500 Characters per message ▪ 32 Message memory ▪ Manually programmable
	<p>7830</p>	<p>SIRIUS 8 Line Alphanumeric Pager</p> <p align="center">SPECIAL PRICING</p> <div style="border: 1px solid black; padding: 5px;"> <p>Technical Specification</p> <p>Code Format.....POCSAG</p> <p>Rx Frequency454-460</p> <p>Nominal Battery Lifemore than 30 days ('AAA' alkaline battery)</p> <p>Bit Rate.....</p> <p>512/1200/2400bps</p> <p>Number of Cap codes..... 6</p> <p>Channel Space Receiver:..... 12.5/25KHz</p> <p>Nominal Battery 'AAA' alkaline battery</p> <p>Low Battery Voltage1.1V</p> <p>LCD8 line x 21chars or 4 line x 17 chars</p> <p>Max Messages 60</p> <p>Max chars per message 500</p> <p>Backlight.....White LED</p> <p>Alarm Daily alarm</p> </div>	<p>Mechanical Specification</p> <p>Unit size (mm): ..72mm(L) 53mm(W) 19mm(H)</p> <p>.....2.8 inch(L) x 2.0inch(W) x 0.75inch (H)</p> <p>Weight 65grams / 2oz</p>
	<p>2010</p>	<p>Big Z-200 Desktop/Vehicle Pager</p>	<p>BIG Z-200 DESKTOP PAGER:</p> <ul style="list-style-type: none"> • Pocsag/Synthesized • Adjustable Volume, Loud Buzzer • 6 Keys Operation, User Friendly Interface • Four Line, available Zoom-In to Two line • Options: 3 AAA Rechargeable Battery for back up

PRODUCT	PART #	DESCRIPTION	
	<p>2873 2874 2885 2886 2886CA</p>	<p><u>VOICE / TONE RECHARGEABLE PAGERS</u></p> <p>Talk-1 Tone/Vibrate Pager Charging Base for Talk-1 Talk-2 Tone/Voice Pager Charging Base for Talk-2 Talk-2 Amplified Charger (not shown)</p>	<p><u>VOICE/TONE PAGERS:</u></p> <ul style="list-style-type: none"> • Single or Dual Channel Option • IP 54 Specification Protection from Rain & Dust • Wideband & Narrowband Capable • 8 Minutes Stored Voice Memory • 4 Position Selector Knobs • Function Mode Announcement • 4 Programmable Tone & Vibrate Alerts • Priority Scan, Normal Scan, Silent Scan Functions • User Programmable Tone for Different Addresses • Channel Monitor Function • Low Battery Alert • Standard Desktop Charger Base • Optional Amplified Charger Base • Earphone Jack • Synthesized
	<p>4413PR 4513LED 4413LED 4413REL</p>	<p><u>WIRELESS LED PAGER DISPLAY SIGNS</u></p> <p>LED Programming Software w/Serial Cable 52" A/N Wireless LED Display 6-3/4"High 28" A/N Wireless LED Display 6-3/4"High 28" A/N Wireless LED Display 6-3/4"High w/Relay</p>	<p><u>LED PAGER:</u></p> <ul style="list-style-type: none"> • Ideal for NurseCall, Commercial, and Industrial Applications such as hotels, office lobbies, shopping malls, theaters, factories, warehouses & churches. • The LED Display signs receive messages like a standard pager. • Send Custom Alphanumeric Messages automatically from NurseCall Systems, Emergency Alert Systems & Alarm Panels. Use Inter Page's Enterprise 101 Software to send a message from any PC. • Use Inter Page's SilentPage Alpha Desktop Transmitter with keyboard to send alpha messages to any LED Sign up to a one mile open air range. • Selectable scroll speeds. • Memory will hold up to 24 messages. • Selectable audio alert for each message. • Internal Clock (Optional)
	<p>2898 2899C 2899PR PRG</p>	<p><u>COASTERS</u></p> <p>Z-15 UHF Coaster / Rechargeable & Stackable 1 to 30 31 - 200 Z-15 Coaster Charging Base (15 coaster capacity) w/ Power Supply Z-15 Coaster Programmer w/Software (Optional) Programming Charge if programmer is not purchased</p>	<p><u>COASTER PAGERS :</u></p> <ul style="list-style-type: none"> • Tone, Vibrate & 14 Flashing LEDs • Uses 2 AAA Ni-MH Rechargeable Batteries • 6 Capcode Addresses • Over the air "Off" Command • Dimensions: 5.12" diameter x 0.66" depth • Charging Base – (Holds 15 coasters) • Weight: 4.09 oz w/batteries
	<p>2894 2896B 2898BC 2898PS 2894Case</p>	<p>Z20 UHF Coaster 1 to 20 21 to 200 Z20 Coaster Charger (20 coaster capacity) Z20 Coaster Battery Cover w/screws Z20 Coaster Charger Power Supply Z20 Coaster Case</p>	<p><u>Features of the Z20 Coasters:</u></p> <p>Tone, vibrate, and 13 LED flashing alert Programmable length and Type of Alerts Each charger can Charge up to 20 Coasters(optional) 4 addresses (with four functions per address) Programmable Alert type Two LED (Heartbeat, Alert, Out of range, Low battery) Ni-MH Rechargeable battery Over the air "off" Synthesized or Crystal Type Business card space to insert Advertisement. The Coaster will be turned off and charging at the same time when it is put in any slot of the desk charger, and turn on automatically when it is picked up Each coaster charger can be extended with multiplication. One adapter can be used for 4 desk</p>

PRODUCT	PART #	DESCRIPTION	
	<p>2199 2199C 2199P</p>	<p><u>PADDLE PAGERS</u></p> <p>Paddle Pager with rechargeable batteries</p> <p>Paddle Pager charger stand with power adapter</p> <p>Programmer</p> <p><u>Charger</u></p> <ul style="list-style-type: none"> • One Desk Charger for 10 paddle pagers. • Extend with additional chargers. • One adapter can be used for desk chargers. • Pager will turn off and charge at the same time when it is put in any slot of the desk charger and will turn on automatically when it is picked up. 	<p><u>PADDLE PAGERS:</u></p> <ul style="list-style-type: none"> • Tone, vibrate, and flashed (6 LED) alert • Over the air " off " • Each charger can hold up to 10 Paddle Pagers • Each adapter can connect up to 4 chargers (option) • 4 addresses (with four functions per address) • Programmable Alert type . • Ni-MH Rechargeable battery • Synthesized • Guest paging • PC Programmable • Advertisement Area Available

UHF Transmitters, Antennas, Receivers and Pagers carry a limited Manufacturer's Warranty against defects for one (1) year including parts & labor.

CALL 800-992-1000

561-844-7900

FAX: 561-844-5844

Email: sales@iplp.com

Web: www.iplp.com