

Tone/Voice Talk-1 Pager

Specifications:

Tone Coding:	2-Tone Sequential
Frequency:	Uhf 406-500 Mhz Narrow band & wide band, VHF 135-174 Mhz
Channel Spacing:	12.5/25KHz
Paging Sensitivity:	5uV per meter
12DB SIAND Sensitivity:	12uV per meter
Adjacent channel Sensitivity:	55dB+/-25KHz
Spurious & Image Rejection:	55dB below carrier
Frequency Stability:	UHF+/-3ppm, VHF +/-10ppm
Alert Tone:	90dBa at 30cm (12")
Voice:	87dBa at 30cm (12")
Power Consumption:	8.2mA (without power saver)
Power Supply:	One 1.5V AA Size Ni-MH rechargeable battery.
Battery Life:	Approx. 20 days (10 days without battery saver)
Dimensions:	3"(D)x2"(W)x3.5"(H)
Weight (w/battery):	Approx. 56.5g
Options:	Single Unit Charger



Pager Part #2873
Charger Part #2874



Special Features:

- Two tone decoding format
- Six (6) call per channel / 4 individual and 2 group call
- Loud & Clear Alert Level
- Large volume control knobs
- Slide switch with on/off, vibrate and alert selection
- Tone and vibrate alert
- Monitor with carrier squelch
- Two (2) status LED:
 - Red LED light flash when alert, LED on means with unread voice.
 - Green LED blink means monitor On, Green LED means audio lock.

