

# **SilentPage Voice/Tone Paging System**



## **Features & Specifications:**

- Desktop Transmitter
- For Numeric, Alphanumeric and Two Tone Voice Paging Applications
- Supports up to 999 Capcodes
- Operates in UHF 450-470 MHz or VHF 147-170 MHz
- Alarm input 7 pins: Dry contact, 0 and 5V low active
- Support COMP1, COMP2, SCOPE, GACOMP2, TAP Protocol
- 99 programmable alpha messages
- Blue Backlit super twist LCD screen with 4 lines
- 1-Watt of power providing 1-2 miles of coverage
- Option Booster to 5 watts of power (TA500)
- RS232 port for serial data and programming
- View last message
- Out of Area signal transmit
- Range test feature optimizes coverage area
- Clock setup
- Hand or PC Programmable
- Individually customizable for each Pager, Capcode, Baud, Alpha, Tone, Function Code, and Group Code for each number
- PBX port with DTMF Telephone Interconnect feature which supports paging via telephone systems (Optional)



7354 Central Industrial Dr., West Palm Beach, FL 33404 \* PH: 561-844-7900 \* FAX: 561-844-5844  
1-800-992-1000 \* [www.iplp.com](http://www.iplp.com) \* sales@iplp.com