

Talk-1.0 Voice Pager



**Talk -1.0 IP 52 Approved Pager
Two Tone Single Channel Heavy Duty**

Quick Battery Charger



Pager Part#2998
Charger Part #2998C

Talk-1.0 Voice Pager

Talk – 1.0

Key Specifications/Special Features:

1. IP52 Approved , Two Tone Decoding Format
2. Six call per channel / 4 individual and 2 group call
3. 120 seconds memory (1-4 stored voice, each for 30 seconds) optional function feature
4. Loud clear alert level: 90dBa at 12 inches distance
5. Large volume control knobs
6. Slide switch with on/off, vibrate, alert selection
7. Tone & vibrate Alert
8. Monitor with carrier squelch
9. Priority alert programmable
10. Monitor channel function
11. Audio lock on
12. One AA Ni-HM rechargeable battery or one AA alkaline battery
13. Desktop charger as standard
14. Fixed alert (not voice) at Maximum alert level
15. Battery low indicate, special beep tone
16. External Earphone Jack 2 Status LED: Red LED Light flash when alert, LED on means with unread voice. Green LED blink means monitor On, Green LED on means audio lock

Other Specifications:

1. Talk – 1.0 Voice Pager
2. Tone Coding: Two -Tone Sequential
3. Frequency: VHF 135~174 MHz, UHF 406~500MHz Narrow band & wide band
4. Channel Spacing : 12.5/25KHz
5. Paging Sensitivity : 5uV per meter
6. 12DB SIAND Sensitivity: 12 uV per meter
7. Adjacent channel selectivity: 55dB ?25KHz
8. Spurious & Image Rejection 55dB below carrier
9. Frequency Stability: VHF ?10ppm, UHF ?3ppm
10. Alert Tone: 90dBa at 30cm(12") Voice 87dBa at 30cm(12")
11. Power Consumption: 8.2mA (without power save) Power Supply One 1.5V AA-Size Ni-MH rechargeable battery
12. Battery Life: About 20 days (10 days without battery saver) Based on 8 hours per day & 5 messages w/ 30 sec. each
13. Dimension: 80(L) x 53(W) x 24.50(H) mm
14. Weight (with battery): Approximately 177g

