

Talk-2.2 Voice Pager



Pager Part#2999
Charger Part #2886C

Synthesized Voice Pager with Caller ID, LCD Display IP54 Approved

For Fire, Police, Hospitals and EMS Personnel

Available in Narrow Band or Wideband Selectable



Talk-2.2 Voice Pager

Key specifications/Special features:

1. Speaker /earphone jack.
2. Twelve call per channel / 8 individual and 4 group call.
3. 480 seconds memory (1 - 16 stored voice, each for 30 sec)optional function feature.
4. Loud clear alert level.
5. Large volume control knobs with on/off Switch
6. Function switch: different function switch will be configured to 4 positions.
7. Two channels
8. Silent & Priority Scan
9. Programmable Narrowband / Wideband Channel Spacing.
10. Caller ID display
11. IP54 Approved

BATTERY CHARGER for Talk 2.2 Pager

Accommodates:	One Talk-3 and spare battery
Adapter Input/output:	AC:100~240Vac, 50~60Hz / DC: 8.4V 600mA
Charger current:	DCA 400mA
Full Recharge Time:	Approximately 2.5 hours
Weight (without battery):	Approximately 175g
Size:	1.54(H) x 2.42 (W)inches

Rich Sophistication:

1. **Loud clear alert level:** 93dBa at 12 inches distance
2. Priority alert programmable
3. Monitor channel function 3 AAA Ni-HM rechargeable battery or 3 AAA alkaline batteries
4. Desktop charger standard
5. Fixed alert (no voice) at maximum alert level Low
6. Battery indicator, strong belt clip
7. Reminder tone with LED flash
8. 6 Status LED + LCD display

Tone Coding: Two -Tone Sequential

Frequency: VHF UHF 135~174MHz
404~512MHz

Wide Band/Narrow Band: WB NB

Channel Spacing: 25KHz/12.5KHz

Alerting: 4uV/m 4uV/m 3.5uV/m 3.5uV/m

Adjacent channel selectivity: 60dB +/-25KHz 50dB +/-
12.5KHz 60dB +/-25KHz
50dB +/-12.5KHz

Spurious Rejection: 60dB below carrier 50dB below
carrier

1'st Image Rejection: 60dB below carrier
50dB below carrier

2'nd Image Rejection: 60dB below carrier 60dB below
carrier

Frequency Stability: +/-10ppm +/- 3ppm

Audio Output: 90dBa at 30cm (12)

Alert Tone: 93dBa at 30cm (12) Power
Consumption: 9mA (without power
save)

Power Supply: One NiMH 3 x 1.2V AAA-size
950mAh rechargeable battery (1.2V)

Battery Lifer:

NiMH About 14 days(7 days without battery
saver) Based on 8 hours Day / 5 message
w/30 sec. each

Weight (with battery): Approximately 6.56 oz

Dimension: 2.75(H) x 2(L) x .75 (W)inches